

PAW-TD20B8E3-1



Det stora utbudet av Aquarea lösningar hjälper dig att göra ditt hem more energisnålt

[LÄS MER](#)

Kombinationstank		ENFAS
Reference		PAW-TD20B8E3-1
Dimension (Height)	mm	1770
Dimension (Width)	mm	640
Dimension (Depth)	mm	690
Weight (empty)	Kg	150
Volume	L	185 + 80
Power supply (Voltage)	V	230
Power supply (Phase)		1
Power supply (Frequency)	Hz	50
Hot water tank - Volume	L	185
Hot water tank - Max working pressure	MPa (bar)	0,8 (8)
Hot water tank - Pressure test	MPa (bar)	1,2 (12)
Hot water tank - Max working temperature	°C	90
Hot water tank - Connections	mm	Ø22
Hot water tank - Material		S 275 JR vitrified
Hot water tank - Insulation (Material)		PUR
Hot water tank - Insulation	t=mm	50
Hot water tank - Heating coil surface	m ²	2,1
Hot water tank - Electrical heater	W	3000
Hot water tank - Energy loss at 65°C	kWh/24h	1,3
Hot water tank - Energy efficiency class (from A+ to F)		B
Hot water tank - Standing loss	W	53
Buffer tank - Volume	L	80
Buffer tank - Max working pressure	MPa (bar)	0,6 (6)
Buffer tank - Pressure test	MPa (bar)	0,9 (9)
Buffer tank - Max working temperature	°C	90
Buffer tank - Connections	mm	Ø22
Buffer tank - Material		S235 JR
Buffer tank - Insulation (Material)		PUR
Buffer tank - Insulation	t=mm	40 mm
Buffer tank - Heating coil surface	m ²	—
Buffer tank - Electrical heater	W	—
Buffer tank - Energy loss at 65°C	kWh/24h	—
Buffer tank - Energy efficiency class (from A+ to F)		B
Buffer tank - Standing loss	W	46

Kompletterande produkter